

| <b>GUARANTEED ANALYS</b> | IS               | 8-0-0-9S      |
|--------------------------|------------------|---------------|
| ACTIVE INGREDIENTS:      | Ammonium Sulfate | 38% by weight |
|                          | Water            | 62% by weight |

# KEEP OUT OF REACH OF CHILDREN – SEEK MEDICAL HELP IF INJESTED – FOR SKIN EXPOSURE, FLUSH WITH WATER

## **Product Information**

Double filtered solution manufactured with high grade Ammonium Sulfate (21-0-0-24) and water. Approved adjuvant for Enlist One®

## **Product Features**

- Ties up antagonistic calcium ions found in hard water
- Provides required levels of ammonium ions for increased plant uptake
- Mixes quickly and easily in cold, hard water conditions

## **Use Rates**

1 gallon Marco 8-0-0-9 equates to 4# ammonium sulfate. Use volumes below for desired ammonium sulfate rates:

- 4.5 gallons AMS/100 gallon =17# ammonium sulfate per 100 gallon
- 3 qt/acre of Marco 8-0-0-9 =3# ammonium sulfate per acre

## Weight per gallon & Storage Requirement

- o 10.2#/gallon
- May be stored below 32°
- Store in stainless steel, fiberglass or fertilizer grade poly tanks

## Ideal For All Herbicides That Benefit From Ammonium Sulfate

## Clip from Liberty® 280 SL Herbicide Label (11-1-17)

Adjuvant • Ammonium sulfate (AMS) can be used at 1.5 lb/A to 3 lb/A. Rates are dependent on tankmix partners, environmental conditions, temperatures and potential for leaf burn. • AMS has shown to improve weed control of difficult-to-control weeds, like velvetleaf and lambsquarters, under difficult environmental conditions (low relative humidity) or hard water. • Anti-foam agent is recommended to control the foaming.

#### **CONDITIONS OF SALE AND WARRANTY**

The Directions for Use of this product are based on field use and tests. The directions are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risks inherently associated with the use of this product. Crop injury, ineffectiveness, or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application all of which are beyond the control of manufacturer or the Seller. All such risks shall be assumed by the Buyer. THE MANUFACTURER OR SELLER MAKES NO OTHER EXPRESSED OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY OF ANY OTHER EXPRESSED OR IMPLIED WARRANTY. IN NO CASE SHALL THE SELLER BE LIABLE FOR CONSEQUENTIAL, SPECIAL, OR INDIRECT DAMAGE RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT. The manufacturer and the Seller offer this product, and the Buyer and User accept it, subject to the foregoing Conditions of Sale and Warranty, which may be varied only by agreement in writing signed by a duly authorized representative of the manufacturer.

